



ISOLATORS (3 POLE) & MCCB NM1 RANGE

* SABS in Accordance to: IEC 60947-2 Standards

LOAD BREAK SWITCH (ISOLATORS) - 3 POLE *

ENVIRONMENTAL TEMPERATURE

Upper Temperature Limit : +40°C • Lower Temperature Limit : 5°C

Average 24 hour Temperature shall not exceed : +35°C • Maximum Rated Voltage : = 690Volt AC 50 Hertz

Part Number	Rated Current (A)	Let Through Current	Dimensions Depth / Length / Width	UNIT PRICE (excl. VAT)
NM1-100SI	100A	25 kA	Depth - 63mm Length - 155mm Width - 90mm	R 726.00
NM1-225SI	160A , 225A, 250A	25 kA	Depth - 86mm Length - 165mm Width - 105mm	R 924.00
NM1-400SI	400A	25 kA	Depth - 104mm Length - 258mm Width - 140mm	R 2,772.00
NM1-630SI	630A	35 kA	Depth - 160mm Length - 270mm Width - 182mm	R 4,620.00
NM1-800HI	800A	65 kA	Depth - 148mm Length - 280mm Width - 210mm	R10,032.00
NM1-1250HI	1000A, 1250A	65 kA	Depth - 205mm Length - 410mm Width - 210mm	R15,840.00



NM1 RANGE
ISOLATOR

NM1 "S" RANGE MOULDED CASE CIRCUIT BREAKERS *

Part Number	Rated Current (A)	Operation Voltage (V)	Short Circuit (Ka)	Dimensions Depth / Length / Width	UNIT PRICE (excl. VAT)
NM1-100S	16A, 20A, 32A, 40A, 50A, 63A, 80A, 100A	690 Volts	25 kA	Depth - 63mm Length - 155mm Width - 90mm	R 792.00
NM1-225S	125A, 150A, 160A, 200A, 225A, 250A	690 Volts	25 kA	Depth - 86mm Length - 165mm Width - 105mm	R 1,056.00
NM1-400S	250A, 315A, 350A, 400A	690 Volts	25 kA	Depth - 104mm Length - 258mm Width - 140mm	R 3,036.00
NM1-630S	500A, 630A	690 Volts	35 kA	Depth - 160mm Length - 270mm Width - 182mm	R 5,280.00



NM1 RANGE
MOULDED CASE CIRCUIT BREAKER (MCCB)