



NM8 ADJUSTABLE MOULDED CASE CIRCUIT BREAKERS



* SABS in Accordance to: IEC 60947-2 Standards

THERMAL MAGNETIC RELEASE (ADJUSTABLE FROM 80% TO 100%) *

ENVIRONMENTAL TEMPERATURE

Upper Temperature Limit : +40°C • Lower Temperature Limit : 5°C
Average 24 hour Temperature shall not exceed : +35°C

APPLICATION

For protection and control of circuits against overloads and short circuits. Suitable for industrial installation.
The breaker can be installed vertically and horizontally.

Thermal Magnetic : Range Adjustable from 0.8 x full load



NM8 RANGE
THERMAL MAGNETIC RELEASE
MOULDED CASE CIRCUIT BREAKER (MCCB)


Part Number	Amp Adjustment	Voltage (V)	kA Rating	Dimensions Depth / Length / Width	UNIT PRICE (excl. VAT)
NM8-125S	80A - 100A 100A - 125A	400V / 690V	50 kA (Ics = Icu)	Depth - 90mm Length - 140mm Width - 79mm	R 1,440.00
NM8-250S	128A - 160A 160A - 200A 200A - 250A	400V / 690V	50 kA (Ics = Icu)	Depth - 105mm Length - 157mm Width - 88mm	R 2,820.00
NM8-400S	252A - 315A 320A - 400A	400V / 690V	70 kA (Ics = Icu)	Depth - 140mm Length - 255mm Width - 113mm	R 5,040.00
NM8-630S	400A - 500A	400V / 690V	70 kA (Ics = Icu)	Depth - 140mm Length - 255mm Width - 113mm	R 6,600.00
NM8-800S	640A - 800A	400V / 690V	50 kA (Ics = Icu)	Depth - 210mm Length - 370mm Width - 196mm	R18,000.00

ELECTRONIC RELEASE (ADJUSTABLE FROM 40% TO 100%) *

APPLICATION

For protection and control of circuits against overloads and short circuits. Suitable for industrial installation.
The breaker can be installed vertically and horizontally.

Electronic : Range Adjustable from 0.4 x full load



NM8 RANGE
ELECTRONIC RELEASE
MOULDED CASE CIRCUIT BREAKER (MCCB)

Part Number	Amp Adjustment	Voltage (V)	kA Rating	Dimensions Depth / Length / Width	UNIT PRICE (excl. VAT)
NM8S-125S	50A - 125A	400V / 690V	50 kA (Ics = Icu)	Depth - 105mm Length - 157mm Width - 88mm	R 5,040.00
NM8S-250S	100A - 250A	400V / 690V	50 kA (Ics = Icu)	Depth - 105mm Length - 157mm Width - 88mm	R 5,880.00
NM8S-400S	160A - 400A	400V / 690V	50 kA (Ics = Icu)	Depth - 140mm Length - 255mm Width - 113mm	R 7,560.00
NM8S-630S	252A - 630A	400V / 690V	50 kA (Ics = Icu)	Depth - 140mm Length - 255mm Width - 113mm	R 9,000.00
NM8S-800S	320A - 800A	400V / 690V	50 kA (Ics=50% Icu)	Depth - 210mm Length - 370mm Width - 196mm	R22,800.00
NM8S-1250S	500A - 1250A	400V / 690V	50 kA (Ics=50% Icu)	Depth - 210mm Length - 370mm Width - 196mm	R29,400.00