

# Moulded Case Circuit Breaker / Isolator



## NM1 "S" Range Moulded Case Circuit Breakers

Code	Rated Current	KA Rating	Dimensions (mm)		
			L	W	D
NM1-125S	16A, 20A, 32A, 40A, 50A, 63A, 80A, 100A	25kA	155	90	63
NM1-250S	125A, 150A, 160A, 200A, 225A, 250A	25kA	165	105	86
NM1-400S	250A, 315A, 350A, 400A	35kA	258	140	104
NM1-630S	500A, 630A	35kA	270	182	160



NM1-125S

## NM1 "H" Range Moulded Case Circuit Breakers

Code	Rated Current	KA Rating	Dimensions (mm)		
			L	W	D
NM1-125H	16A, 20A, 32A, 40A, 50A, 63A, 80A, 100A	50kA	155	90	86
NM1-250H	125A, 150A, 160A, 200A, 225A, 250A	50kA	165	105	103
NM1-400H	250A, 315A, 350A, 400A	50kA	257	150	107
NM1-630H	500A, 630A	50kA	270	182	111
NM1-800H	630A, 700A, 800A	60kA	280	210	107
NM1-1250H	1000A, 1250A	65kA	406	210	141



NM1-1250H

## NM1S - Load Break (Isolators) - 3 Pole

Code	Rated Current	Dimensions (mm)		
		L	W	D
NM1-125SI	100A	155	90	63
NM1-250SI	160A, 225A, 250A	165	105	86
NM1-400SI	400A	258	140	104
NM1-630SI	630A	270	182	160
NM1-630SI	800A	280	210	148
NM1-630SI	1000A, 1250A	410	210	205



NM1-250SI