



AU-1M



AU-4M

Auxiliary Contacts

Code	Applicable	Type	Auxiliary Contacts
AU1M01	GMC-6 ~ 16M GMD-6 ~ 16M	Side Mount	1NC
AU1M10			1NO
AU2M02		Top Mount	2NC
AU2M20			2NO
AU2M11			1NO + 1NC
AU4M04			4NC
AU4M13			1NO + 3NC
AU4M22			2NO + 2NC
AU4M31			3NO + 1NC
AU4M40			4NO



AT-12M

Electronic Top Mount Timer

Code	Applicable	Voltage	Type	Range
AT-12M	GMD-6~16M	AC/DC 24-48V	On-delay	0,1 - 30 sec
AT-12M/2	GMC-6~16M	AC/DC 24-48V	Off-delay	0,1 - 30 sec
AT-12M/3	GMC-6~16M	AC100-220V	On-delay	0,1 - 30 sec
AT-12M/4	GMC-6~16M	AC100-220V	On-delay	0,1 - 30 sec

Surge Absorber Unit



AS-12M

Code	Applicable	Voltage
AS-12M/1	GMC-6~16M	AC12 - 48V
AS-12M/2	GMC-6~16M	AC60 - 127V
AS-12M/3	GMC-6~16M	AC200 - 240V
AS-12M/4	GMD-6~16M	DC12 - 24V
AS-12M/5	GMD-6~16M	DC30 - 72V
on request	GMD-6~16M	DC100 - 127V
on request	GMD-6~16M	DC200 - 250V