

Miniature Thermal Overload (Type:GTK-12M)

Code	Applicable	Rated Current	
		AC3 380~440VAC	
		Mid Range	Range
GTK12M/00.14A	GMC-6 ~ 16M GMD-6 ~ 16M	0.14A	0.1 - 0.16A
GTK12M/00.21A		0.21A	0.16 - 0.25A
GTK12M/00.33A		0.33A	0.25 - 0.4A
GTK12M/00.52A		0.52A	0.4 - 0.63A
GTK12M/00.82A		0.82A	0.63 - 1A
GTK12M/01.3A		1.3A	1 - 1.6A
GTK12M/02.1A		2.1A	1.6 - 2.5A
GTK12M/03.3A		3.3A	2.5 - 4A
GTK12M/05A		5.0A	4 - 6A
GTK12M/06.5A		6.5A	5 - 8A
GTK12M/07.5A		7.5A	6 - 9A
GTK12M/08.5A		8.5A	7 - 10A
GTK12M/11A		12A	9 - 13A
GTK12M/14A		14A	12 - 16A
AZ12MH	GTK12M	Separate mounting unit	



GTK-12M



GMC-0616

Coils for miniature contactor

Code	Applicable	Type	Voltages
GMC-0616-*	GMC-6 ~ 16M	AC	12V, 24V, 48V, 110V, 240V, 415V
GMD-0616-*	GMD-6 ~ 16M	DC	12V, 24V, 48V, 110V, 250V

* Specify the voltage when placing order ie(GMC-0616-415V)

AR12M



Interlocking Device

Code	Applicable	Description
AR12M	GMC-6 ~ 16M GMD-6 ~ 16M	Miniature contactor interlocking unit