



TS800N FMU

## Susol FMU adjustable moulded case circuit breakers (3 Pole)

Code	Rated Current	Short Circuit	Dimensions (mm)		
			H	W	D
TS100N	16A, 20A, 25A, 32A, 40A, 50A, 63A, 80A, 100A, 125A, 160A	415V=50kA	90H	14W	86D
TS160N	16A, 20A, 25A, 32A, 40A, 50A, 63A, 80A, 100A, 125A, 160A	415V=50kA	90H	14W	86D
TS100N FMU	100A, 125A, 160A, 200A, 250A	415V=50kA	105H	160W	86D
TS250N FMU	100A, 125A, 160A, 200A, 250A	415V=50kA	105H	160W	86D
TS400N FMU	300A, 400A, 500A, 630A	415V=50kA	140H	260W	110D
TS630N FMU	300A, 400A, 500A, 630A	415V=50kA	140H	260W	110D
TS800N FMU	800A	415V=50kA	210H	320w	135D



TS160N ETS

## Susol ETS Electronic MCCB (3 pole)

Code	Rated Current	Short Circuit	Dimensions (mm)		
			H	W	D
TS160N ETS	160A	415V=50kA	105	160	86
TS250N ETS	250A	415V=50kA	105	160	86
TS400N ETS	400A	415V=50kA	140	260	135
TS630N ETS	630A	415V=50kA	140	260	135
TS800N ETS	800A	415V=50kA	210	327	185,3
TS1000N ETS	1000A	415V=50kA	210	327	185,5
TS1250N ETS	1250A	415V=50kA	210	327	185,5
TS1600N ETS	1600A	415V=50kA	210	327	185,5

## Susol DTU Moulded Case Isolators (3 pole)

Code	Rated Current	Short Circuit	Dimensions (mm)		
			H	W	D
TS100NA	100A	415V=50kA	105	160	86
TS160NA	160A	415V=50kA	105	160	86
TS250NA	250A	415V=50kA	105	160	86
TS400NA	400A	415V=50kA	140	260	110
TS630NA	630A	415V=50kA	140	260	110
TS800NA	800A	415V=50kA	140	260	110



TS100NA