

TSD Series (Single Phase)

Code	TSD-3000	TSD-5000	TSD-7000
Rated Capacity (kVA)	3	5	7
Rated Input Voltage (V)	160-250	160-250	160-250
Overload protective current (A)	15	15	15
230V Voltage Stabilising Accuracy	±3%	±3%	±3%
110V Voltage Stabilising Accuracy	±6%	±6%	±6%
Over-Voltage protection	246 ±4	246 ±4	246 ±4
Under-Voltage protection	184 ±4	184 ±4	184 ±4
Delay time (min)	5 ±2	5 ±2	5 ±2
Voltage Regulating speed	7,5	7,5	7,5
Power Factor	0,8	0,8	0,8
* Wall mountable			

Wall Mountable



TSD-5000

SBW-100



- Input voltage: 400V (1±20%)
- Output voltage: 400V (1±3%) (Adjustable)
- Frequency: 50~60Hz
- Precision of Voltage Regulation: ±(1~5)% (Adjustable)
- Time of Response: 0.5s
- Efficiency: 98%
- Free Standing

SBW Series - (Three Phase)

Code	Rating	Dimensions (mm)			Weight Kg
		L	W	H	
SBW-030	30kVA	750	570	1250	230
SBW-050	50kVA	800	570	1375	285
SBW-100	10kVA	850	570	1450	408
SBW-150	150kVA	1150	570	1900	630
SBW-180	180kVA	1150	570	1900	660
SBW-200	200kVA	1150	570	1900	700
SBW-250	250kVA	1150	570	1900	780
SBW-300	300kVA	1180	570	2050	950
SBW-350	350kVA	1300	570	2250	1000
SBW-400	400kVA	1300	570	2250	1100
SBW-450	450kVA	1300	570	2250	1400
SBW-500	500kVA	1300	570	2250	1450
SBW-600	600kVA	1300	1000	2250(x2)	800x2
SBW-800	800kVA	1150	850	2200(x3)	950x3
SBW-1000	1000kVA	1150	850	2200(x3)	1000x3
SBW-1200	1200kVA	1150	850	2200(x4)	1000x4
SBW-1300	1300kVA	1150	850	2200(x4)	1020x4
SBW-1500	1600kVA	1150	850	2200(x4)	1100x4